



GRAB STRAP

FITTING/ USER INSTRUCTIONS

Contact: Enduro World
Tel: +27 (0) 87 808 7192
Email: info@enduroworld.co.za
Website: www.enduroworld.co.za

Congratulations on your new **ENDURE GRAB STRAP**. The strap requires a little handy work to install, but should only take you about 15 minutes or so.

The strap is made from quality webbing with a breaking strength of 800 kg, however you have to make a hole in it which reduces the strength. For most bikes the webbing should be long enough to enable doubling the end over before making the hole and bolting it on. This will give it added strength.

As with all our products, **ENDURE** aims to keep improving and developing the **GRAB STRAP** so we invite and encourage you to give us feedback and let us know of any problems or suggestions you may have after using the product.

NOTE: We recommend getting off your bike and using this strap as little as possible - it is far better to stay on your bike, roll back and use good riding technique to clear the obstacle, than to have to get off the bike and use valuable physical strength/ energy to manhandle the bike. Still there are times when this strap will come in handy.

The strap should be allowed to dry and air out after washing/ getting wet.

Please follow fitting instructions herein.



1. You should be able to find suitable mounting bolts on your bike - either seat-mounting bolts (Yamaha/ Jap bikes) or the fender-securing bolts under the rear fender (KTM/ Husqvarna).
2. Centre and align the strap with the selected bolts.
3. Keeping just enough space to get your fingers under the strap, mark the strap where the bolts will go through it.



4. To make the holes in the webbing, use either a soldering iron or heat up an old phillips screw driver with a blowtorch, candle or lighter, then push the heated tip through the doubled webbing.

6. Using the washers supplied, bolt the strap in place (longer bolts may be required in some cases).